TECHNICAL DATA SHEET

Burlington®
Yesterday's designs TODAY'S TECHNOLOGY

Claremont Angled Bath Shower Mixer - deck mounted

[T9]	Angled Bath Shower Mixer (Including the standard cradle, 'S' adjuster, Claremont, Anglesey & Birkenhead divertor handle, hose, ceramic telephone handset , excluding tap heads, base and unions)
[T18]	Deck Mounting unions (for Bath Shower Mixer & Bath Filler, 3/4
[T1]	Claremont tap handles (pair)

Product Specification

Finishes	Chrome plated
Product Type	Traditional
Material	Bodies are of all brass construction

Additional Information

Supplied with flow straighter - this is for use with low water pressure
Supplied with aerator - this is for use with high water pressure

System Pressure	.2 bar	.5 bar	1.0 bar	2.0 bar	3.0 bar
with flow straightener*	22.00	22.60	25.20	27.20	29.00
with aerator*	5.60	10.70	11.60	14.30	15.60

* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap

Guarantee

10 YEAR GUARANTEE

See our website for terms and conditions

Compliance / Approvals

BS 5412:1996
Specification for low-resistance single taps and combination tap assemblies (nominal size ? and ?) suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)
BS EN 200:2008
Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification